he

DAS

Waterbase Inks



More open screen time means production can keep rolling.



Waste Less

Oasis inks won't dry out halfway through your print run.



Meet Standards

Non-PVC, Non-Phthalate: Designed to meet the unique regulatory and print performance requirements.

 $\mathsf{T}N$



Hit Colors

WPC Color Mixing system support delivers bright, opaque colors for improved color match accuracy.

Talk Shop

The best technical support team in the business has your back.

China PolyOne China No. 1, QiHang Industrial Park Haoxiang Road, Shajing Town Baoan District, Shenzhen 518104 Guangdong, China Tel: +86 755 2969 2888 Fax: +86 755 2969 2999

England PolyOne Corporation UK Ltd Units 9-11 Unity Grove Knowsley Business Park Knowsley, Merseyside, L34 9GT United Kingdom Tel: +44 (0) 151 547 6051 Fax: +44 (0) 151 632 8807

USA PolyOne 8155 Cobb Center Drive Kennesaw, GA 30152 Tel: 770.590.3500 Tel: 800.326.0226 Fax: 678.290.2749

Wilflex Tech Services 1-800-321-0226, press 1 techserviceswilflex@polyone.com



PolyOne ©2013 PolyOne Corporation All Rights Reserved. Wilflex™ inks by PolyOne.





Wilflex Oasis Discharge

Discharge Inks

Discharge Activator Discharge Base Discharge Blending White Discharge Super White

The Oasis Discharge ink line consists of discharge inks that are activated with Oasis Discharge Activator. Oasis Discharge inks can be used on dischargeable cotton fabrics to produce exceptional results with bright color development and an excellent soft hand feel

- Super soft hand feel with good color fastness and durability.
- Excellent discharge with bright color results.
- Can be used with Oasis Hydrate inks to yield soft prints with vibrant long-lasting color.
- WPC color mixing system support.

Wilflex[™] Oasis



Wilflex Oasis Hydrate

High Solid Waterbase Inks

Hydrate Neutral Hydrate White Hydrate HO White

Oasis Hydrate inks are high solids water-based printing inks designed to provide excellent hand and opacity. The addition of Oasis waterbase pigments (WPC) will result in strong color development, soft hand and excellent wash and crock fastness.

- Non-PVC, Non-Phthalate, Non-Formaldehyde.
- Excellent screen "open" time.
- Smooth, matte surface with minimal tack.
- ▶ Flashes dry and fast.
- Good elongation.
- Superior wash and crock fastness.
- Can be used with Oasis Discharge to yield soft prints with vibrant long-lasting color.
- WPC Color Mixing System support.

Wilflex Oasis Hydrosoft

Soft Hand Inks for White & Light Garments

Hydrosoft Base

Oasis Hydrosoft Base is a water-based printing ink designed to produce superb soft hand prints with excellent fine detail for halftone graphics. The addition of Oasis waterbase pigments (WPC) will result in strong color development, excellent hand, and good wash and crock fastness on white and light fabrics.

- Non-PVC, Non-Phthalate, Non-Formaldehyde.
- Super soft hand with excellent color fastness and durability.
- Excellent fine detail for halftone graphics.
- Wet-on-wet printing capabilities.
- WPC color mixing system support.

Wilflex Oasis Additives

Oasis Saturate

Designed for use with Oasis inks when ink penetration is desired.

Oasis Retarder

Designed to extend the screen life of Oasis inks.

Oasis Softener

Designed to enhance and further soften the hand feel of Oasis inks.

Oasis Thickener

Designed to be used with Oasis inks to enhance flow properties.

Wilflex Oasis Color Mixing

Pigments

Wilflex[™] Oasis Pigments (WPCs) are concentrated waterbase colorants designed for use with the Wilflex Oasis family of inks.

- High strength, designed for bright color development and color match accuracy.
- Consistent low viscosity across all pigments for easy handling.
- ▶ 15 Standard WPCs for use with the Oasis family of inks.

China

PolyOne China No. 1, QiHang Industrial Park Haoxiang Road, Shajing Town Baoan District, Shenzhen 518104 Guangdong, China Tel: +86 755 2969 2888 Fax: +86 755 2969 2999

England

PolyOne Corporation UK Ltd Units 9-11 Unity Grove Knowsley Business Park Knowsley, Merseyside, L34 9GT United Kingdom Tel: +44 (0) 151 547 6051 Fax: +44 (0) 151 632 8807

USA PolyOne 8155 Cobb Center Drive Kennesaw, GA 30152 Tel: 770.590.3500 Tel: 800.326.0226 Fax: 678.290.2749

Wilflex Tech Services 1-800-321-0226, press 1 techserviceswilflex@polyone.com



